TRIPTON®
Oil & Grease - Car Care Products

TRIPTON Motor Oils - SAE 10W, 30, 40, 50 and 60 ; API SF

DESCRIPTION:
TRIPTON MOTOR OILS, SAE 10W, 30, 40, 50 and 60 are manufactured using carefully selected premium high viscosity index base oils combined with a high performance additive package with optimal blending of dispersants, oxidation and corrosion inhibitors, extreme pressure anti-wear, viscosity improver, and de-foaming additives.

FEATURES/BENEFITS:
TRIPTON MOTOR OILS, SAE 10W, 30, 40, 50 and 60 are exceptional, premium quality "universal" crankcase oils recommended for gasoline and light diesel engines operating under severe service and subjected to varying operation and climatic conditions.

APPLICATIONS:
TRIPTON MOTOR OILS, SAE 10W, 30, 40, 50 and 60 are suitable for use where the following specification is recommended API SF.
TRIPTON MOTOR OILS, SAE 10W is suitable for use in my hydraulic system.

Physical and Chemical Properties

Property	ASTM Methods	Values	Values	Values	Values	Values
SAE Grade	-	10W	30	40	50	60
API Service	-	SF	SF	SF	SF	SF
Density @15 °C/ g/mL	D1298	> 0.840	> 0.870	> 0.870	> 0.870	> 0.870
Viscosity Index	D2270	> 90	> 90	> 90	> 90	> 90
Viscosity @ 40 °C; cSt	D445	> 25.8	> 96.7	> 165	> 208	> 342
Viscosity@100 °C; cSt	D445	> 4.6	> 10.5	> 15.0	> 19.0	> 24.0
Pour Point °C	D97	< -30	< - 20	< -18	< -12	< -12
Evap. Loss (Noak Weight loss after 1h at 250°C) max	D5800	18	17	15	13	10
Flash Point (COC) °C	D92	> 210	> 230	> 230	> 235	> 240
Foaming Seq I/Seq II/Seq III	D892	10/50/10 0/0/0	10/50/10 0/0/0	10/50/10 0/0/0	10/50/10 0/0/0	10/50/10 0/0/0
TBN mg KOH/g	D2896	> 7.5	> 7.5	> 7.5	> 7.5	> 7.5
Phosphorus/ wt.%	D1091	> 0.06	> 0.06	> 0.06	> 0.06	> 0.06
Sulfated Ash %w	D874	> 1.3	> 1.3	> 1.3	> 1.3	> 1.3

The above values may vary within commercially accepted tolerances.

+1 (714) 391-4679
+(962) 795 505-101
info@tripton1.com
www.tripton1.com
Irvine - California
USA