TRIPTON®
Oil & Grease - Car Care Products

AUTOMATIC TRANSMISSION FLUID - DEXRON-III

DESCRIPTION:
TRIPTON METALLIC DEXRON-III is a multipurpose ATF designed for new generation, electronically controlled transmissions. It meets the latest GM Dexron III Specification. It meets the performance requirements of the major hydraulic manufacturers' requirements for anti-wear hydraulic fluids.

FEATURES/BENEFITS:
- Optimized frictional properties.
- Excellent wear performance, Outstanding oxidation stability, No foaming, and Excellent low temperature properties.

APPLICATIONS:
TRIPTON METALLIC DEXRON-III may be recommended for the following uses:
- When Dexron III , Dexron II, or Type A Fluids are required.
- When Mercon, M2C138-CJ or M2C166-H Fluids are required.
- Can be used in some hydraulic and compressor systems where excellent low temperature flow ability is required.

Physical and Chemical Properties

Property	ASTM Methods	Values
SAE Grade	-	20
Performance	-	GM- Dexron III
Density @15 °C/ g/mL	D1298	> 0.840
Viscosity @ 40 °C; cSt	D445	Min 36
Viscosity@100 °C; cSt	D445	Min 7.0
Viscosity Index	D2270	min 160
Pour Point °C	D97	< -40
Flash Point (COC) °C	D92	> 180
TBN mg KOH/g	D2896	> 0.5
TAN mg KOH/g	D974	< 1.2
Foaming; Seqs. I/ II/ III	D892	< 25/50/25 0/0/0
Cu Strip Corro.; 3h @ 150°C	D130	1B

The above values may vary within commercially accepted tolerances.

+1 (714) 391-4679
+(962) 795 505-101
info@tripton1.com
www.tripton1.com
Irvine - California
USA