TRIPTON® AUTOMATIC TRANSMISSION FLUID (ATF)
TRIPTON® ATF-DEX-CVT

DESCRIPTION:

TRIPTON® METALLIC ATF DEX-CVT is Fully synthetic automatic transmission fluid (ATF) of excellent quality and long-standing, specially formulated using high quality base oils and additives to be used in modern Continuous Variable transmission (CVT) drives.

TRIPTON® METALLIC ATF DEX-CVT is produced using high quality base oils and a special additive technology developed specifically to meet the special requirements of CVT drives with push and pull belts.

FEATURES/BENEFITS:

- Optimized frictional properties.
- Excellent wear performance, Outstanding oxidation stability, No foaming, and Excellent low temperature properties.

APPLICATIONS:

TRIPTON® METALLIC ATF DEX-CVT may be recommended for the following uses:

- Japanese Automobiles with belt and chain-driven CVTs.
- Passenger cars with belt-driven continuously variable transmissions (CVTs).
- Always use METALLIC ATF DEXRON-CVT as recommended ATF-CVT, If it's not available, you may use a METALLIC DEXRON III as a temporary replacement.

- **Not suitable for Automobiles with Toroidal or Dry CVTs.**
- **It is not recommended for eCVT or in any non-CVT transmission.**

Please refer to the owner's manual for correct transmission fluid recommendation

Physical and Chemical Properties

Property	ASTM Methods	Values
SAE Grade	-	12
Performance	-	HONDA ATF-Z1
Density @15 °C/ g/mL	D1298	> 0.840
Viscosity @ 40 °C; cSt	D445	Min 27
Viscosity@100 °C; cSt	D445	6.0-7.5
Viscosity Index	D2270	min 160
Pour Point °C	D97	< -45
Flash Point (COC) °C	D92	> 180
TBN mg KOH/g	D2896	> 0.5
TAN mg KOH/g	D974	< 1.5
Foaming; Seqs. I/ II/ III	D892	< 25/50/25 (0/0/0)
Cu Strip Corro.; 3h @ 150°C	D130	1B

The above values may vary within commercially accepted tolerances.

+963 983690474 info@tripton1.com
+963 993401222 www.tripton1.com
Adra Industrial City – Chemical 2
Damascus-Syria

Packing:
The products are available in the following:

Code	TRL421215-01	TRL421215-02	TRL421215-05	TRL421215-06
Pack (L)	200 L	20 L	4 L	1 L

Expiration date: *The recommended shelf life for these oils is typically 5 years from manufacturing date when stored properly in the original sealed containers.*

HANDLING AND STORAGE

Precautions for safe handling: Keep away from sources of ignition. No naked lights. No smoking. Do no eat, drink or smoke when using this product. Wash hands and other exposed areas with soap and water before leaving work. **Specific end use(s):** Use only as ATF-CVT Oils.	**Storage:** All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety & Environment
Health and Safety

TRIPTON® Products are no any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment: Take used oil to an authorized collection point. Do not discharge into drains, soil or water.