TRIPTON® HIGH TEMPERATURE GREASE
SUPERB Grease NGLI 0, 1, 2, 3, 4 or 5

DESCRIPTION:

TRIPTON® HIGH TEMPERATURE GREASE is a premium NLGI 1, 2, or 3 multipurpose, inorganic/organic thickeners and extreme pressure (EP) grease that provides outstanding high temperature performance and excellent lubrication over a high temperature range and variety of services including heavy duty fleets, automotive, farm and industrial application.

FEATURES/BENEFITS:

TRIPTON® HIGH TEMPERATURE GREASE:

- Provides excellent water resistance, Rust and Corrosion protection, excellent oxidation resistance, and wear protection under extreme loads
- Resists softening due to heat, Resists separation and pumps easily,
- Mixture of the Inorganic and organic thickeners give high dropping point grease.

Physical and Chemical Properties		**TRL735201**	**TRL735202**	**TRL735203**
	ASTM'S	**SUPERB Grease NGLI 1**	**SUPERB Grease NGLI 2**	**SUPERB Grease NGLI 3**
Aspect		smoothy	smoothy	smoothy
Color		RED	RED	RED
Thickener (%)		Inorganic/organic	Inorganic/organic	Inorganic/organic
NLGI grade		1	2	2
DIN 51 502		MP 1 N-30	MP 2 N-30	MP 3 N-30
Type of base oil (White OILS)		GROUP 1	GROUP 1	GROUP 1
Kine. Visc. of base oil @ 40°C (CST)	D445	46-100	46-100	46-100
Utilization limits (°C)		- 30 to 140	- 30 to 140	- 30 to 140
Penetration - at 25 °C (0.1 mm)	D 217	310-340	265-295	220-250
Dropping point (°C)	D566	> 240	> 240	> 240
Copper strip Corrosion (24h @100 °C)	D4048	1	1	1
4-Balls weld Load (KgF)	D2596	>200	>200	>200
Rust Test	D1743	PASS	PASS	PASS
The above values may vary within commercially accepted tolerances.				

Packing:

The products are available in the following:

Code	**TRL73520n-01**	**TRL73520n-11**
Pack (KG)	**170 kg**	**11 kg**

Expiration date: *The recommended shelf life for these oils is typically 5 years from manufacturing date when stored properly in the original sealed containers.*

HANDLING AND STORAGE

Precautions for safe handling: Keep away from sources of ignition. No naked lights. No smoking. Do no eat, drink or smoke when using this product. Wash hands and other exposed areas with soap and water before leaving work. **Specific end use(s): Can be used as Lubricant in the Industrial Apps.**	**Storage:** All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety & Environment

Health and Safety

TRIPTON® Products are no any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment: Take used lubricants to an authorized collection point. Do not discharge into drains, soil or water.