TRIPTON® ISO Hydraulic Fluid WSL 15

DESCRIPTION:

TRIPTON® ISO Hydraulic Fluid WSL 15 is quality hydraulic fluid formulated from base stocks incorporated with selected additives designed for weight indicator sensors, lubricators on rig floor, mud pump and stand pipe pressure gauge, etc.

FEATURES/BENEFITS:

TRIPTON® ISO Hydraulic Fluid WSL 15 is efficient anti-wear oils, fully inhibited with anti-oxidation, anti-corrosion, anti-rust and anti-foam additives. Superior anti-rust characteristics protect pump lines and controls against rust and corrosion. They exhibit excellent demulsification properties even above moderate temperature levels, still maintaining the ability to reject water.

APPLICATIONS

TRIPTON® ISO Hydraulic Fluid WSL 15 is recommended weight indicator sensors, lubricators on rig floor, mud pump and stand pipe pressure gauge, etc.

Physical and Chemical Properties

CODE		**TRL320642**
Property	**ASTM's**	**WSL 15**
ISO Viscosity Grade	**D2432**	**15**
Color	**D1500**	**Red; 5.5-6.5**
Density @15 °C/ g/mL	D1298	>0.820
Viscosity @ 40 °C; cSt	D445	13.5-16.5
Viscosity Index, mini	D2270	95
Pour Point °C, max	D97	-40
Flash Point (COC) °C, mini.	D92	180
Foaming (Seq I/Seq II/Seq III)	D892	20/50/20 (0/0/0)
TAN mg KOH/g	D974	< 0.35
Cu Strip Corrosion (3h@ 100ºC)	D130	2
Demulsibility time (40/3/37) max	D1401	30 min @ 54 ºC
Water Content (%)	D1744	<0.025

The above values may vary within commercially accepted tolerances.

Packing:

The products are available in the following:

Code	TRL320642-01	TRL320642-02
Pack (L)	200 L	20 L

Expiration date: *The recommended shelf life for these oils is typically 5 years from manufacturing date when stored properly in the original sealed containers.*

HANDLING AND STORAGE

Precautions for safe handling: Keep away from sources of ignition. No naked lights. No smoking. Do no eat, drink or smoke when using this product. Wash hands and other exposed areas with soap and water before leaving work. **Specific end use(s): Use only as Hydraulic oils.**	**Storage:** All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety & Environment

Health and Safety

TRIPTON® Products are no any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Protect the Environment: Take used oil to an authorized collection point. Do not discharge into drains, soil or water.